Calculating Recommended Weight Limit (RWL) Fact Sheets



WHAT IS THE REVISED NIOSH LIFTING EQUATION?

The equation is:

 $LC \times HM \times VM \times DM \times AM \times FM \times CM = RWL$

where LC is the load constant (23 kg) and other factors in the equation are:

- HM, the Horizontal Multiplier factor
- VM, the Vertical Multiplier factor
- DM, the Distance Multiplier factor
- FM, the Frequency Multiplier factor
- AM, the Asymmetric Multiplier factor
- CM, the Coupling Multiplier factor
- RWL, the Recommended Weight Limit

For each value, look up the corresponding factor and use this number in the equation. See Assessing Relevant Handling Factors for explanation of terms.

To use the calculator, click on the values for each factor in the left hand column (or you can input your numbers directly into the second equation). Press the "Calculate RWL" button when you have finished selecting all of the values.

Horizontal Multiplier (HM): Horizontal distance (H, in cm) from the midpoint between the ankles to the hands while holding the object.


H = Horizontal Distance (cm)	HM Factor
25 or less	1.00
30	0.83
40	0.63

50	0.50
60	0.42



Vertical Multipler (VM): The vertical distance (V, in cm) of the hands from the ground at the start of the lift.

V = Starting Height (cm)	VM Factor	
0	0.78	
30	0.87	
50	0.93	
70	0.99	
100	0.93	
150	0.78	
175	0.70	
>175	0.00	



Distance Multipler (DM): The vertical distance (D, in cm) that the load travels.

D = Lifting Distance (cm)	DM Factor
25 or less	1.00
40	0.93
55	0.90
100	0.87
145	0.85
175	0.85
>175	0.00

DM 25 or less ▼

Asymmetric Multipler (AM): The twisting angle (A) of the body while lifting, measured in degrees.

A = Angle (degrees)	AM Factor	
90°	0.71	
60°	0.81	
45°	0.86	
30°	0.90	
0°	1.00	




Frequency Multipler (FM): The frequency (F) of lifts and the duration of lifting (in minutes or seconds) over a workshift.

	FM Factor			
F = Time Between Lifts			OR Lifting While Stooping:	
	One Hour or Less	Over One Hour	One Hour or Less	Over One Hour
5 min	1.00	0.85	1.00	0.85
1 min	0.94	0.75	0.94	0.75
30 sec	0.91	0.65	0.91	0.65
15 sec	0.84	0.45	0.84	0.45
10 sec	0.75	0.27	0.75	0.27
6 sec	0.45	0.13	0.45	-
5 sec	0.37	_	0.37	-

FM = pick a value from (A) and (B).

(A) Time Between Lifts Lifting While Standing

⊙0ne Hour or Less
○0ver One Hour
Lifting While Stooping
○0ne Hour or Less
○0ver One Hour



Coupling Multipler (CM): The quality of grasp (or coupling, C) classified as good, fair or poor and depends on the body position (either standing or stooping).

C = Cross	CM Factor:		
C = Grasp	Standing	Stooping	
Good (handles)	1.00	1.00	
Fair	1.00	0.95	
Poor	0.90	0.90	

(A)StandingCM = pick a value from (A) and (B).

(A) ⊙Standing
○Stooping



The revised NIOSH Lifting Equation is: 23 Kg \times HM \times VM \times DM \times AM \times FM \times CM= RWL

or, input values directly in the equation below:

Reset Form

Source: © Copyright 1997-2021 CCOHS